Document No: B880 Edition: 1

Date: 2019-0'
Page: 1(1)
Prepared: MS

Approved:

1 Industrivägen 10 2019-07-30 SE-792 32 Mora Sweden 1(1) +46 250 94900 MS info@alocenter.se

ALO Center AB

www.alocenter.se



ALO 880

ALO 880

AN

Electrical powered band saw coiler

A universal model currently introduced as standard to all our machines handling coils of band saw blades. The plate of aluminum has machined slots to facilitate bundling and loading/un-loading coils with hoist equipment or similar.

Foldable protection rolls that enclose the coil are included as well.

An electric motor with integrated frequency control as regulated in combination with a speed regulation arm ensures a very even and smooth operation, no matter if it operates with an ALO machine or as a "stand-alone" installation.

ALO 880 has a pushbutton control mounted to the stand with functions for emergency stop, jog function and direction selection clockwise winding (CW) or counterclockwise winding (CCW).

The coiler are available in several different configurations, see below specification.

SELECT: ALO 90915/90915-S/90916/90916-S/90917/90918

Expandable centre with auto band lock

 Coil center
 Expanded size

 90915
 320 mm

 90915-S
 320 mm

 90916
 450 mm

 90916-S
 450 mm

 90917
 500 mm

 90918
 400 mm





Expanded center

Collapsed center

Legend 880-X-Y:

880= Electrical drive 881=No drive, manually adjusted friction break

(X=A) Take up (left to right oriented) Pay off (right to left oriented) (X=B) Take up (right to left oriented) Pay off (left to right oriented)

(Y=1) Band holder arm (Y=2) Speed regulation arm (Y=3) Band holder arm and Speed regulation arm

Common for all 880 versions:

Drive motor system: Electric
Coiler OD: 1000mm
Size from floor to band back: 1100mm
Coiler height adjustment: ±20 mm
Air pressure: 6.3bar

Space requirement(I x w x h): 1300 x 1100x 1200mm

Weight: 185 kg

Standard voltage: 400VAC ±10% 3-phase, 50-60 Hz ±1% directly earthed system,

other voltages available upon request.

Model 881 have no drive motor but instead manually adjusted friction break

Standard configurations for our machines:

881 (pay off) and 880-B-2 (take up) for all ALO 191 models 880-A-2 and 880-B-3 are standard coiler for ALO 184 models 880-CTL are standard for ALO 177 Cut to length machine



CE

SWEDISH QUALITY
WITH RESPECT FOR THE
ENVIRONMENT AND
SAFETY REGULATIONS