

ALO 880-CTL

Electrical powered band saw coiler


ALO 880-CTL is design to operate together with ALO's cut to length machines.

The plate of aluminum has machined slots to facilitate bundling and loading/un-loading of coils with hoist equipment or similar.

The coiler has a safe protective guarding for a secure work environment and can be lowered when loading or unloading coils. Foldable protection rolls that enclose the coil are included as well.

An electric motor with integrated frequency control as regulated in combination with a band holder arm and a speed regulation arm ensures a very even and smooth operation, no matter if it operates with an ALO machine or as a "stand-alone" installation.

ALO 880 has a pushbutton panel mounted on the stand with functions for emergency stop, jog function and direction selection clockwise winding (CW) or counterclockwise winding (CCW).



Several different expandable coiling center's including auto band end locking device are available as option.

SELECT: **ALO 90915/90915-S/90916/90916-S/90917/90918**

Expandable centre with auto band lock

Coil center	Expanded size
90915	320 mm
90915-S	320 mm
90916	450 mm
90916-S	450 mm
90917	500 mm
90918	400 mm



Expanded center



Collapsed center

TECHNICAL SPECIFICATION:

Drive motor system:	Electric
Coiler OD:	1000mm
Size from floor to band back:	1100mm
Coiler height adjustment:	±20 mm
Air pressure:	6.3bar
Space requirement(l x w x h):	1300 x 1100x 1200mm
Weight:	215 kg
Standard voltage:	400VAC ±10% 3-phase, 50-60 Hz ±1% directly earthed system, other voltages available upon request.

